




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification⁶ : C09J 7/02 // A47L 25/00</p>	<p>A1</p>	<p>(11) International Publication Number: WO 98/37160</p> <p>(43) International Publication Date: 27 August 1998 (27.08.98)</p>
<p>(21) International Application Number: PCT/US97/09946</p> <p>(22) International Filing Date: 9 June 1997 (09.06.97)</p> <p>(30) Priority Data: 08/806,186 25 February 1997 (25.02.97) US</p> <p>(71) Applicant: MINNESOTA MINING AND MANUFACTURING COMPANY [US/US]; 3M Center, P.O. Box 33427, Saint Paul, MN 55133-3427 (US).</p> <p>(72) Inventor: WOOD, Thomas, L.; P.O. Box 33427, Saint Paul, MN 55133-3427 (US).</p> <p>(74) Agents: LEVINE, Charles, D. et al.; Minnesota Mining and Manufacturing Company, Office of Intellectual Property Counsel, P.O. Box 33427, Saint Paul, MN 55133-3427 (US).</p>		<p>(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).</p> <p>Published With international search report.</p>

(54) Title: PROGRESSIVELY PERFORATED TAPE ROLL



(57) Abstract

A tape (12) includes a backing layer (22) and an adhesive layer (24) formed on the backing layer. A plurality of lines of perforations (32) extend across the tape to separate the tape (12) into sheets. The sheets have progressively increasing lengths such that, when the sheets are wound into a roll (10), each sheet is longer than the sheet underneath it. When in a roll, the outermost sheet covers all of the lines of perforations to reduce instances of the tape tearing in a downweb direction.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

PROGRESSIVELY PERFORATED TAPE ROLL

5

TECHNICAL FIELD

The present invention relates to tape rolls. More particularly, the present invention relates to perforated tape rolls.

10

BACKGROUND OF THE INVENTION

Most rolls of tape are used by first removing a length of tape from the roll before using the tape for its intended purpose. Typically, a length of tape is peeled from the roll and is cut for use. In some applications, the tape is used while on the roll and is removed after use.

Lint removal tape is used while still on a roll to remove lint and other small particles from fabric, such as clothing. The tape is removed from the roll only after use, to discard it. In roll form, lint removal tape is typically wound on a core with the adhesive side of the tape wound outwardly for use. A roll of lint removal tape is generally used on an applicator. Various lint removal tape rolls are known, such as those described in U.S. 5,027,465 and U.S. 5,388,300.

Rolls of tape are often perforated for easier removal of individual sheets. Material that has perforations and is wound into a roll becomes wavy and distorted because the perforations create a high spot in the roll due to pushed up material. Aligning perforations on a roll with each line of perforations substantially radially above the line of perforations on the sheet below it forms a lump in the roll. With a roll of 60 sheets, this can create a lump over 0.63 cm

(0.25 in) high. This makes the roll out-of-round, making the roll difficult to unwind and use.

Also, with aligned lines of perforation, a user has difficulty determining which sheet to grab to
5 remove a sheet. The user may grab more than one sheet, wasting material and often causing the material to tear improperly, in a downweb, longitudinal direction. Improper tearing also occurs without aligned
10 perforations, where sheets have equal length and an outer sheet does not necessarily cover the adjacent inner sheet. There is a need for a perforated tape roll with improved cross-web tearability.

SUMMARY OF THE INVENTION

15 A length of tape has a first longitudinal end, a second longitudinal end, a first side edge, and a second side edge. The tape includes a backing layer and an adhesive layer on the backing layer. The tape is formable into a roll having a plurality of wraps.

20 A plurality of lines of perforations extend across at least most of the width of the tape between the first and second side edges to separate the tape into sheets. The sheets have progressively increasing lengths from the first end to the second end such that,
25 when the sheets are wound into a roll, each sheet is longer than the sheet underneath it.

When the tape forms a roll, the outermost sheet has a free, leading edge and a trailing end defined by a line of perforations. The outermost sheet covers all
30 of the lines of perforations. The line of perforations that defines the trailing end of the outermost sheet prevents the outermost sheet from adhering tightly to itself. This reduces instances of the tape tearing in a downweb direction.

35

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a perspective view of a roll of tape of the present invention.

Figure 2 is a top view of a portion of tape.

5 Figure 3 is a side view of the tape of Figure 2.

Figure 4 is a side view of the roll of tape of Figure 1.

DETAILED DESCRIPTION

10 Figures 1-3 show a roll 10 of lint removal tape 12. As shown in Figure 2, the tape 12 has a first longitudinal end 14, a second longitudinal end 16, a first side edge 18, and a second side edge 20. As shown in Figure 3, the tape is formed of at least two
15 layers, a backing layer 22 and an adhesive layer 24 and can be made from any known materials. The tape is formable into a roll having a plurality of wraps.

The backing layer 22 has a first side 26 and a second side 28 and can be made of, for example, paper
20 or plastic film. Suitable paper backings include saturated flatstock and crepe. Suitable plastic film backings include polypropylene, polyethylene, copolymers of polypropylene and polyethylene, polyesters, and vinyl acetates. The polypropylene can
25 be biaxially oriented polypropylene (BOPP) or simultaneously biaxially oriented polypropylene (SBOPP). The backing material can be compostible, degradable, colored, printed, and can be of different surface textures or embossed.

30 The adhesive layer 24 is placed on the first side 26 of the backing layer 22. It can be formed on the entire first side, or the backing layer can be uncoated by adhesive along one or both side edges. Alternatively, the side edges can be adhesive coated

and then detackified by using waxes, lacquers, or inks for example.

The adhesive can include hotmelt-coated formulations, transfer-coated formulations, solvent-coated formulations, and latex formulations. Useful adhesives according to the present invention include all pressure sensitive adhesives. Pressure sensitive adhesives are normally tacky at room temperature and can be adhered to a surface by application of, at most, light finger pressure. Examples of adhesives useful in the invention include those based on general compositions of polyacrylate; polyvinyl ether; diene-containing rubber such as natural rubber, polyisoprene, and polyisobutylene; polychloroprene; butyl rubber; butadiene-acrylonitrile polymer; thermoplastic elastomer; block copolymers such as styrene-isoprene and styrene-isoprene-styrene block copolymers, ethylene-propylene-diene polymers, and styrene-butadiene polymer; poly-alpha-olefin; amorphous polyolefin; silicone; ethylene-containing copolymer such as ethylene vinyl acetate, ethylacrylate, and ethyl methacrylate; polyurethane; polyamide; epoxy; polyvinylpyrrolidone and vinylpyrrolidone copolymers; polyesters; and mixtures of the above. Additionally, the adhesives can contain additives such as tackifiers, plasticizers, fillers, antioxidants, stabilizers, pigments, diffusing particles, curatives, and solvents.

A general description of useful pressure sensitive adhesives may be found in Encyclopedia of Polymer Science and Engineering, Vol. 13, Wiley-Interscience Publishers (New York, 1988). Additional description of useful pressure sensitive adhesives may be found in Encyclopedia of Polymer Science and Technology, Vol. 1, Interscience Publishers (New York, 1964).

The tape 12 is formed into a roll 10 having a plurality of wraps with the adhesive layer 24 facing outwardly by rolling the tape on only itself. Support material, such as a core, a liner, or any other
5 material that could lend support and provide rigidity and strength to the roll of tape, is optional. In the illustrated embodiments, none is used.

The roll 10 of tape could also include a third layer. A low adhesion backside (LAB) layer 30 can be
10 formed on the second side 28 of the backing layer 22 to facilitate removing the outer wrap of tape from the roll 10. Suitable LAB layers include silicones, fluorochemicals, acrylates, and polyvinylacetates. Numerous other layers can be added to the tape, such as
15 primers to increase the adhesion of adhesive layer 24 to backing layer 22. Also, printed material can be located on the first side of the backing layer under the adhesive, or on the second side of the backing layer either under or over any LAB layer 30. This
20 printed material can be advertising, instructions, or other information. The tape could contain deodorants, perfumes, antistatic materials, and encapsulated cleaning chemicals. Also, the backing layer 22 can be modified by flame treatment, corona treatment, and
25 roughening.

A plurality of lines of perforations 32 divide the tape into discrete sheets, to help remove the outer wrap of tape from the roll 10. The perforations 32 are made before the tape 12 is formed into a roll 10. Each
30 sheet is defined by the first and second side edges 18, 20, and two adjacent lines of perforations 32.

There are n lines of perforations 32 extending across at least most of the width of the tape 12 between the first and second side edges 18, 20 to
35 separate the tape into $n+1$ sheets. The plurality of

lines of perforations 32 can extend partially or completely across the width of the tape. The sheets have progressively increasing lengths from the first longitudinal end 14 to the second longitudinal end 16
5 such that when the sheets are wound into a roll each sheet is longer than the sheet underneath it.

When the tape 12 forms a roll 10, the outermost sheet 34 has a free, leading edge 36 and a trailing end 38 defined by a line of perforations. As shown in
10 Figure 4, the outermost sheet 34 covers all of the lines of perforations 32. Starting from the inside of the roll 10, each line of perforations 32 can be said to advance with each additional wrap of tape. When the tape is wound into a roll, each sheet completely covers
15 the sheet before it.

The line of perforations that defines the trailing end 38 of the outermost sheet prevents the outermost sheet from adhering tightly to itself. This reduces instances of the tape tearing in a downweb direction
20 nonparallel to the line of perforations. This occurs because the perforations act as a detackified area. In one embodiment (such as where the perforating knife has a longer side on the downweb side of the tape), during the perforating process, at least some of the
25 perforations in each line create folded over material (with adhesive facing down, away from the outer sheets), are slightly higher, and have holes. These features individually and in combination act as a detackified area. Also, a pull roll can be overdriven
30 to elongate the perforated area and make a larger detackified area. Thus, the line of perforations below the outermost sheet (which define the trailing end of the outermost sheet) helps remove this sheet.

An overlap (the distance the line of perforations 32 of the trailing end 38 is being behind the leading edge 36 of the outermost sheet 34) of approximately 0.3175 cm (0.125 in) works well to assist tearability.

- 5 An overlap of more than 1.270 cm (0.500 in) or an underlap (the distance the line of perforations 32 of the trailing end 38 is ahead of the leading edge 36 of the outermost sheet 34) do not assist tearability.

- 10 Any number of perforations can be used to create the line and any shape and length for the perforations can be used. A perforator using a high performance motion control system can be designed to create sheets of increasing length. The control system changes the speed of the perforator to add the necessary length to
- 15 successive sheets. This length is compounded until the desired sheet count is attained. The control system then automatically resets the sheet count and length to the start of a new roll. With an overlap length of approximately 0.3175 cm (0.125 in), each sheet should
- 20 be 0.3175 cm + 0.076 cm (0.125 in + 0.030 in) longer than the previous sheet. The 0.076 cm (0.030 in) (which is π times twice the thickness of the tape) is added to compensate for the larger roll diameter as the tape is wound (for a tape width of 0.0122 cm (0.0048
- 25 in) and a starting diameter of 4.45 cm (1.75 in)).

- Various changes and modifications can be made in the invention without departing from its scope or spirit. For example, although the illustrated embodiments show coreless rolls of lint removal tape,
- 30 the invention can be used with cored rolls of lint removal tape, other rolls of tape wound adhesive side out, and rolls of tape wound adhesive side in.

CLAIMS

1. A length of tape 12 having a first longitudinal end 14, a second longitudinal end 16, a first side edge 18, and a second side edge 20 and comprising:

a backing layer 22 having a first side 26 and a second side 28;

an adhesive layer 24 on the first side 26 of the backing layer 22, wherein the tape 12 is formable into a roll 10 having a plurality of wraps; and

a plurality of lines of perforations 32 extending across at least most of the width of the tape 12 between the first and second side edges 18, 20 to separate the tape into sheets, wherein the sheets have progressively increasing lengths from the first longitudinal end 14 of the tape to the second longitudinal end 16 of the tape such that, when the sheets are wound into a roll 10, each sheet is longer than the sheet underneath it by an overlap length.

2. The tape 12 of claim 1 wherein the tape is wrapped into a roll 10 with the outermost sheet 34 having a free, leading edge 36 and a trailing end 38 defined by a line of perforations 32, wherein the outermost sheet covers all of the lines of perforations.

3. The tape 12 of claim 1 wherein the line of perforations 32 that defines the trailing end 38 of the outermost sheet 34 prevents the outermost sheet from adhering tightly to itself to reduce instances of the tape tearing in a downweb direction nonparallel to the line of perforations, wherein at least some of the perforations comprise folded over material with

adhesive facing down, away from the outer sheets to create a slightly higher detackified area.

4. The tape 12 of claim 1 wherein each sheet,
5 compared to the adjacent sheet closer to the first longitudinal end 14, is longer by an amount equal to π times twice the thickness of the tape plus a selected overlap length.

10 5. The tape 12 of claim 1 wherein the plurality of lines of perforations 32 extend across the entire width of the tape from the first side edge 18 to the second side edge 20.

15 6. A roll 10 of tape 12 wherein the tape has a first longitudinal end 14, a second longitudinal end 16, a first side edge 18, and a second side edge 20, the roll of tape comprising:




20 a backing layer 22 having a first side 26 and a second side 28;

an adhesive layer 24 on the first side 26 of the backing layer 22, wherein the tape is formed into a roll 10 having a plurality of wraps; and


25 a plurality of lines of perforations 32 extending across at least most of the width of the tape 12 between the first and second side edges 18, 20 to separate the tape into sheets such that starting from the inside of the roll, each line of perforations 32 can be said to advance with each additional wrap of
30 tape to create sheets having progressively increasing lengths from the first longitudinal end 14 of the tape to the second longitudinal end of the tape 16, wherein when the sheets are wound into a roll, each sheet is longer than the sheet underneath it by an overlap
35 length.

7. A length of substrate 12 having a first longitudinal end 14, a second longitudinal end 16, a first side edge 18, and a second side edge 20, wherein
5 the substrate is formable into a roll 10 having a plurality of wraps and comprising a plurality of lines of perforations 32 extending across at least most of the width of the substrate between the first and second side edges 18, 20 to separate the substrate into
10 sheets, wherein the sheets have progressively increasing lengths from the first longitudinal end 14 of the substrate to the second longitudinal end 16 of the substrate such that, when the sheets are wound into a roll, each sheet is longer than the sheet underneath
15 it by an overlap length.

1/2

**Fig. 1****Fig. 2****Fig. 3**

2/2

**Fig. 4**

1

INTERNATIONAL SEARCH REPORT

International application No.

PCT/US 97/09946

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: C09J 7/02 // A47L 25/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: C09J, A47L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5388300 A (PATRICK HICKEY), 14 February 1995 (14.02.95)	1-7
	--	
A	US 5027465 A (NICHOLAS D. MCKAY), 2 July 1991 (02.07.91)	1-7
	--	
A	WO 9506450 A1 (MINNESOTA MINING AND MANUFACTURING COMPANY), 9 March 1995 (09.03.95)	
	-- -----	

☐

Further documents are listed in the continuation of Box C.

☒

See patent family annex.

* Special categories of cited documents:

- * "A" document defining the general state of the art which is not considered to be of particular relevance
- * "B" earlier document but published on or after the international filing date
- * "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- * "O" document referring to an oral disclosure, use, exhibition or other means
- * "P" document published prior to the international filing date but later than the priority date claimed

* "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

* "X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

* "Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

* "&" document member of the same patent family

Date of the actual completion of the international search

28 October 1997

Date of mailing of the international search report

18. 11. 97

Name and mailing address of the ISA/



European Patent Office, P.B. 5818 Patentlaan 2
NL-2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

SOFIA NIKOLOPOULOU

INTERNATIONAL SEARCH REPORT

S 164705

Information on patent family members

01/10/97

International application No.

PCT/US 97/09946

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5388300 A	14/02/95	AT 120627 T CA 2107871 A,C DE 4234609 C DE 59300122 D EP 0592890 A,B ES 2071525 T JP 2595452 B JP 6339452 A	15/04/95 15/04/94 23/12/93 00/00/00 20/04/94 16/06/95 02/04/97 13/12/94
US 5027465 A	02/07/91	AU 626550 B AU 3660889 A CA 1322831 A CA 2045975 A,C DE 3919899 A DE 8910883 U FR 2632846 A,B FR 2678505 A,B GB 2220841 A GB 2257618 A,B JP 2071721 A NZ 229622 A NZ 243211 A US 4905337 A	06/08/92 21/12/89 12/10/93 29/12/92 28/12/89 03/05/90 22/12/89 08/01/93 24/01/90 20/01/93 12/03/90 28/08/95 28/08/95 06/03/90
WO 9506450 A1	09/03/95	AU 7678694 A AU 7718794 A BR 9407375 A CA 2148250 A CA 2169623 A EP 0670705 A EP 0716586 A JP 8505557 T JP 9502111 T US 5496605 A US 5616387 A WO 9506449 A	22/03/95 22/03/95 16/07/96 09/03/95 09/03/95 13/09/95 19/06/96 18/06/96 04/03/97 05/03/96 01/04/97 09/03/95